

Rubberflex Ultra-grip Specification Sheet

Description:

Rubberflex Ultra-grip urethane adhesive is a trowelable, environmentally safe, methylene bisphenyl diisocyanate (MDI) based adhesive. Stronger and faster than traditional solvent-based or water based adhesives. Ideal for installation of rubber flooring, linoleum sheet goods, linoleum tiles and cork flooring.

Outstanding Features:

- Chemically cross-linked; outstanding toughness.
- Excellent adhesion to a variety of substrates.
- Durable; for use indoors or outdoors; will not become brittle.
- Low odor and will not attack concrete subfloors.

Application:

Prior to use, the adhesive should be kept tightly sealed and dry to prevent moisture contamination. Make sure the surfaces to be bonded are clean and free of dirt or foreign materials. Wear rubber gloves when using adhesive, cured adhesive is difficult to remove. Apply adhesive when temperatures are above 40°F. Spread adhesive evenly using a 3/32" square notched trowel; coverage 75-80 sq.ft. gallon. Install flooring onto wet adhesive. Press firmly on flooring to remove curl or bubbles. Flooring must be rolled using 50-100 lb. roller in 45 minutes to insure proper adhesive transfer. Do not spread more adhesive than can be covered with flooring within 30 minutes. **(Open time of adhesive is 30-40 minutes)**. Temperature and high humidity will shorten the open time. Clean adhesive smudges from flooring immediately before adhesive cures. Clean all tools with mineral spirits before adhesive cures. Reseal unused, uncured adhesive in original container with 2 pieces of plastic prior to reattaching the lid.

Centaur Floor Systems

135 Chapala Street • Santa Barbara, CA 93101 • 800-536-9007 • Fax 805-957-0125